



PDG-DWL2500

- Brightness: 2500 ANSI Lumen
- Contrast Ratio: 2000:1
- Resolution: WXGA (1280 x 800)
- 3D Ready DLP chip
- 6 Segment colour wheel
- Extreme Short Throw (80" diagonal image at 2.4cm)
- Network control and Monitoring
- Security Bar (Will allow up to a 10mm Cable)

PDG-DWL2500

TECHNICAL DETAILS

Category	PDG-DWL2500 Business and Education
Panel	0.65" DLP
Lamp	275w
Brightness ANSI lumens	2500
Lamp Service Life	3000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	28dBA (Eco Mode), 36dBA (Normal Mode)
Standard Lens	F=2.5, f=4.83mm
Throw Distance Ratio	0.19:1
Throw Distance	80" diagonal @ 2.4cm
Contrast Ratio	2000:1
Resolution in pixels	1280 x 800
Image size min-max (diagonal)	60" – 110"
Uniformity	78%
Bandwidth/Frequency	150MHz, Horizontal 15kHz – 93kHz, Vertical 50Hz – 120Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Inputs: 1 x HDMI 2 x Dsub15 (1 Switchable) 1 x S-video 1 x RCA (Composite Video) Audio In: 2 x RCA 2 x Mini Jack Outputs: 1 x Dsub15 (Switchable) 1 x 3D Sync Audio Out: 1 x Mini Jack Control: 1 x Dsub9 (RS232) 1 x LAN (RJ45)
Keystone Correction	Vertical $\pm 5^\circ$
HDTV Signals	480i, 480p, 575i, 575p, 720p, 1035i, 1080i
Computer Compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	Fixed / Manual
Power Consumption/Voltage	305w (Eco Mode), 375w (Normal Mode), 0.85w (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	321 x 178 x 386
Weight	6.2kg
Standard Accessories	Quick reference Guide, Owners manual (CD ROM), Computer Cable (Dsub15-Dsub15) Power cable, Remote control
Optional Accessories	POA-CA-SCART (Scart – VGA Cable)

* You can use the distance calculator at www.uk.sanyo.com to determine exact image sizes and distances



4 Castle Terrace, Edinburgh, EH1 2DP
T. 0131 228 2295 F. 0131 228 3823

9 Octavian Way, Team Valley Trading Estate, Gateshead, NE11 0HZ
T. 0191 491 3300 F. 0191 487 1218

PO Box 2900, Stowmarket, Suffolk, IP14 4LL
T. 0845 119 1905 F. 0131 228 3823