



PLC-WL2500

- Brightness: 2500ANSI Lumen
- Resolution: WXGA (1280 x 800)
- Short throw Projector, 80" diagonal image @ 86cm
- Long life air filter, up to 4000 hours
- 10w built in audio amplifier and speaker
- Screen aspect Ratio selection, 4:3, 16:9, 16:10
- Security Bar (Will accept up to a 10mm cable)

PLC-WL2500

TECHNICAL DETAILS

Category	PLC-WL2500 Business and Education
Panel	0.59" Polysilicon TFT (16:10)
Lamp	230w
Brightness ANSI lumens	2500 (Normal Mode), 1900 (Eco Mode)
Lamp Service Life	4000h (Eco Mode), 3000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 36dBA (Normal Mode)
Standard Lens	F=1.8, f=6.68mm
Throw Distance Ratio	0.50:1
Throw Distance	0.64m – 1.2m
Contrast Ratio	500:1
Resolution in pixels	1280 x 800
Image size min–max (diagonal)	60" – 110"
Uniformity	80%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: 2 x Dsub15 (1 switchable to monitor out) 1 x HDMI 1 x S-video 1 x RCA (composite Video) Audio: 1 x Mini Jack 2 x RCA 1 x Mini Jack (Audio out) Control: 1 x D-sub9 (RS232) 1 x RJ45 (LAN)
Keystone Correction	Vertical $\pm 20^\circ$
HDTV Signals	480p, 575p, 720p (50/60), 1080i (50/60), 1080p (50/60)
Computer Compatibility	WUXGA, WSXGA+, WXGA+, WXGA, UXGA, SXGA+, XGA, SVGA, VGA
Zoom/Focus	Manual focus
Power Consumption/Voltage	217w (Eco Mode), 316w (Normal Mode), 0.78w (Standby Mode)
Warranty	3 year
Dimensions (W x H x D)	350 143 x 382mm
Weight	4.6kg
Standard Accessories	Owners Manual (CD ROM), Power Cable, Remote Control, Computer Cable (Dsub15 – Dsub15)
Optional Accessories	POA-CA-COMPVGA (Component – VGA Cable), POA-CA SCART (Scart – VGA Cable)



4 Castle Terrace, Edinburgh, EH1 2DP
T. 0131 228 2295 F. 0131 228 3823

9 Octavian Way, Team Valley Trading Estate, Gateshead, NE11 0HZ
T. 0191 491 3300 F. 0191 487 1218

PO Box 2900, Stowmarket, Suffolk, IP14 4LL
T. 0845 119 1905 F. 0131 228 3823