



PLC-XD2200

- Brightness: 2200 ANSI Lumen
- Resolution: 1024 x 768 (XGA)
- Network Control and Monitoring
- Long Lamp life, up to 6000 hours
- Auto Setup
- PIN Code Security

PLC-XD2200

TECHNICAL DETAILS

Category	Business and Education
Panel	3 x 0.55" TFT Polysilicon (4:3)
Lamp	215w UHP
Brightness ANSI lumens	2200
Lamp Service Life	6,000h (Eco Mode), 4000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 34.3dBA (Normal Mode)
Standard Lens	F=2 – 2.15, f=18.38 – 22.06mm
Throw Distance Ratio	1.62 – 1.92:1
Throw Distance	1.3m – 11.8m
Contrast Ratio	500:1
Resolution in pixels	1024 x 768 (XGA)
Image size min–max (diagonal)	40" – 300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: 1 x Dsub15 (Analog RGB, Component, S-Video) 1 x Dsub15 (Analog RGB, Monitor Out) 1 x RCA (Composite Video) 1 x Mini Jack (Audio in Computer) 2 x RCA (Audio in Video) 1 x Mini Jack (Audio Out) 1 x Dsub9 (RS232 Control) 1 x RJ45 (LAN connection)
Keystone Correction	Vertical $\pm 30^\circ$
HDTV Signals	1080i/50, 1080i/60, 1035i, 720p
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	1.2x / Manual
Power Consumption/Voltage	181w (Eco Mode), 218w (Normal Mode), 247w (High Mode), 0.7w (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	333.5 x 94.2 x 247mm
Weight	2.6kg
Standard Accessories	Quick Ref Guide, Owners Manual (CD ROM), Power Cable, Remote Control
Optional Accessories	POA-CA-COMPVGA (3 RCA – Dsub15 Cable), POA-CA-VGAS (S-Video – Dsub15 Cable), POA-CA-SCART (Scart – Dsub15 Cable)



4 Castle Terrace, Edinburgh, EH1 2DP
T. 0131 228 2295 F. 0131 228 3823

9 Octavian Way, Team Valley Trading Estate, Gateshead, NE11 0HZ
T. 0191 491 3300 F. 0191 487 1218

PO Box 2900, Stowmarket, Suffolk, IP14 4LL
T. 0845 119 1905 F. 0131 228 3823