



## PLC-XE34

- Brightness: 1500 ANSI Lumen
- Resolution: 1024 x 768 (XGA)
- Network Control and Monitoring
- Long Lamp life, up to 6000 hours
- Auto Setup
- PIN Code Security

## PLC-XE34

### TECHNICAL DETAILS

|                               |  |
|-------------------------------|--|
| Category                      | Business and Education   |
| Panel                         | 3 x 0.55" TFT Polysilicon (4:3)  |
| Lamp                          | 215w UHP   |
| Brightness ANSI lumens        | 1500   |
| Lamp Service Life             | 6,000h (Eco Mode), 4000h (Normal Mode)   |
| Fan Noise                     | 29dBA (Eco Mode), 34.3dBA (Normal Mode)  |
| Standard Lens                 | F=2 – 2.15, f=18.38 – 22.06mm  |
| Throw Distance Ratio          | 1.62 – 1.92:1  |
| Throw Distance                | 1.3m – 11.8m   |
| Contrast Ratio                | 500:1  |
| Resolution in pixels          | 1024 x 768 (XGA)   |
| Image size min–max (diagonal) | 40" – 300"   |
| Uniformity                    | 85%  |
| Bandwidth/Frequency           | 140MHz, Horizontal 15kHz – 100kHz, Vertical 50Hz – 100Hz   |
| Colour Systems                | NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N   |
| Connections                   | Inputs: 1 x Dsub15 (Analog RGB, Component, S-Video)<br>1 x Dsub15 (Analog RGB, Monitor Out)<br>1 x RCA (Composite Video)<br>1 x Mini Jack (Audio in Computer)<br>2 x RCA (Audio in Video)<br>1 x Mini Jack (Audio Out)<br>1 x Dsub9 (RS232 Control)<br>1 x RJ45 (LAN connection) |
| Keystone Correction           | Vertical $\pm 30^\circ$  |
| HDTV Signals                  | 1080i/50, 1080i/60, 1035i, 720p  |
| Computer Compatibility        | WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC  |
| Zoom/Focus                    | 1.2x / Manual  |
| Power Consumption/Voltage     | 181w (Eco Mode), 218w (Normal Mode), 247w (High Mode), 0.7w (Standby Mode)   |
| Warranty                      | 3 Year   |
| Dimensions (W x H x D)        | 333.5 x 94.2 x 247mm   |
| Weight                        | 2.6kg  |
| Standard Accessories          | Quick Ref Guide, Owners Manual (CD ROM), Power Cable, Remote Control   |
| Optional Accessories          | POA-CA-COMPVGA (3 RCA – Dsub15 Cable), POA-CA-VGAS (S-Video – Dsub15 Cable), POA-CA-SCART (Scart – Dsub15 Cable)   |



4 Castle Terrace, Edinburgh, EH1 2DP  
T. 0131 228 2295 F. 0131 228 3823

9 Octavian Way, Team Valley Trading Estate, Gateshead, NE11 0HZ  
T. 0191 491 3300 F. 0191 487 1218

PO Box 2900, Stowmarket, Suffolk, IP14 4LL  
T. 0845 119 1905 F. 0131 228 3823